

Silicon NPN Power Transistors

2SC3281

DESCRIPTION


- With TO-3PL package
- Complement to type 2SA1302

APPLICATIONS

- Power amplifier applications
- Recommended for 100W high fidelity audio frequency amplifier output stage

PINNING

PIN	DESCRIPTION
1	Base
2	Collector;connected to mounting base
3	Emitter

Absolute maximum ratings($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V_{CBO}	Collector-base voltage	Open emitter	200	V
V_{CEO}	Collector-emitter voltage	Open base	200	V
V_{EBO}	Emitter-base voltage	Open collector	5	V
I_C	Collector current		15	A
I_B	Base current		1.5	A
P_C	Collector power dissipation	$T_C=25$	150	W
T_j	Junction temperature		150	
T_{stg}	Storage temperature		-55~150	

Silicon NPN Power Transistors

2SC3281

CHARACTERISTICS

Tj=25 unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{(BR)CEO}$	Collector-emitter breakdown voltage	$I_C=50mA ; I_B=0$	200			V
V_{CEsat}	Collector-emitter saturation voltage	$I_C=8A ; I_B=0.8A$			2.5	V
V_{BE}	Base-emitter voltage	$I_C=8A ; V_{CE}=5V$			1.5	V
I_{CBO}	Collector cut-off current	$V_{CB}=200V ; I_E=0$			5	μA
I_{EBO}	Emitter cut-off current	$V_{EB}=5V ; I_C=0$			5	μA
h_{FE-1}	DC current gain	$I_C=1A ; V_{CE}=5V$	55		160	
h_{FE-2}	DC current gain	$I_C=8A ; V_{CE}=5V$	35			
f_T	Transition frequency	$I_C=1A ; V_{CE}=5V$		25		MHz
C_{OB}	Collector output capacitance	$f=1MHz ; V_{CB}=10V$		270		pF


◆ h_{FE-1} classifications

R	O
55-110	80-160

Silicon NPN Power Transistors

2SC3281

PACKAGE OUTLINE



Silicon NPN Power Transistors

2SC3281




Fig.3 Static Characteristic




Fig.4 DC current Gain




Fig.5 Collector-Emitter Saturation Voltage




Fig.6 Safe Operating Area